

# Fire Hose, Standpipes, Hydrants, Branchpipes & Ancillaries



## LAYFLAT FIRE HOSE

Walker Fire non-percolating lay flat hose which conforms to BS 6391 is available in three types: Type 1 is a synthetic jacketed un-coated fire hose with internal EPDM rubber lining. Type 2 is a synthetic jacketed fire hose with a red external elastomeric coating and internal EPDM rubber lining. Type 3 is of unified construction with a polymer compound covering both sides of a synthetic yarn reinforcement. All are supplied with 2 1/2" wired on instantaneous couplings.

## ALSO AVAILABLE

- Full range of branchpipes & nozzles
- Hose racks
- Hydrants
- Couplings
- Bar & keys

For any further information on any of the above products phone your local Walker Fire representative free.

DIAMETER (mm)	STANDARD LENGTHS (metres)	MAX WORKING PRESSURE	BURST PRESSURE
<b>TYPE 1</b>			
38	30	15 bar	50 bar
65	30	15 bar	50 bar
<b>TYPE 2</b>			
65	23 and 30	15 bar	50 bar
<b>TYPE 3</b>			
65	23 and 30	15 bar	50 bar

**FREEPHONE: UK 0800 731 36 30 IRELAND 1800 200 901**