



GPFH.EX2764
Dry-chemical Extinguishers, Wheeled, Marine

Page Bottom

Dry-chemical Extinguishers, Wheeled, Marine

See General Information for Dry-chemical Extinguishers, Wheeled, Marine

AMEREX CORP
 7595 GADSDEN HWY E
 PO BOX 81
 TRUSSVILLE, AL 35173 USA

EX2764

Cartridge-activated-type Extinguishers

Model	Nominal Agent Capacity, lb	Min Use Temp, °F	USCG Classification	
			Type A	Type B:C
Ammonium phosphate				
470, 467, 450	125	-65	Size II	Size V
491	300	-65	Size II	Size V
Potassium bicarbonate				
452, 469, 472	125	-65	—	Size V
493	300	-65	—	Size V
Sodium bicarbonate				
451, 468, 471	150	-65	—	Size V
492	350	-65	—	Size V

Stored-pressure-type Extinguishers

Model	Nominal Agent Capacity, lb	Min Use Temp, °F	USCG Classification	
			Type A	Type B:C
Ammonium phosphate				
495	50	-40	Size II	Size V
488	125	-65	Size II	Size V
573	250	-40	Size II	Size V
Potassium Bicarbonate				
497	50	-40	—	Size V
689, 690	125	-40	—	Size V
490	125	-65	—	Size V
575	250	-40	—	Size V
Sodium bicarbonate				

496	50	-40	—	Size V
489	150	-65	—	Size V
574, 579	250	-40	—	Size V

Last Updated on 2010-12-27

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".