



HMRZ.EX2586 Gate Valves

[Page Bottom](#)

Gate Valves

[See General Information for Gate Valves](#)

NIBCO INC

EX2586

WORLD HEADQUARTERS
1516 MIDDLEBURY ST
PO BOX 1167
ELKHART, IN 46515 USA

- O. S. and Y. pattern, Series T-104-0, bronze body, 1/2 to 2 in. incl. with threaded (T) ends.
- O. S. and Y. pattern, Series (*)-607-0, iron body, 2-1/2 to 12 in. incl. with threaded (T) and flanged (F) ends.
- O. S. and Y. pattern, Series (*)-607-0TS, iron body, 2-1/2 to 12 in. incl. with threaded (T) and flanged (F) ends.
- O. S. and Y. pattern, Series F-607-0I, iron body, 65, 80, 100, 125, 150, 200, 250 and 300 mm sizes with ISO flange ends.
- O. S. and Y. pattern, Series F-607-0TSI, iron body, 65, 80, 100, 125, 150, 200, 250, 300 mm sizes with ISO flange ends.
- O. S. and Y. pattern, Series F-697-0, iron body, 2-1/2 to 10 in. incl. for rated pressure of 350 psig with flanged ends.
- O. S. and Y. pattern, Model 607-RW, resilient wedge, ductile iron body, 2-1/2, 3, 4, 6, 8, 10, 12 in. sizes for a rated pressure of 250 psig with flanged ends.
- N.R.S. pattern, Series M-609, iron body with post indicator flange, 4 to 12 in. incl. with mechanical ends.
- N.R.S. pattern, Series F-609, iron body with post indicator flange, 4 to 12 in. incl. with flanged ends.
- N.R.S. pattern, Series F-609-I, iron body with post indicator flange, 65, 80, 100, 125, 150, 200, 250 and 300 mm sizes with ISO flange ends.
- N.R.S. pattern, model 609-RW, resilient wedge, ductile iron body, 4, 6, 8, 10, 12, in. sizes for a rated pressure of 250 psig with flanged or mechanical joint ends.

[Last Updated](#) on 2007-10-17

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".